

TECHNICAL INFORMATION

AW4131TR V-30



Track Mounted
Adjustable

Application Descriptions:

- Track Mounted, Adjustable
- Internal Areas
- Spotlighting for Retail, Hospitality, Showrooms and Galleries, Reception Areas, Residential Living Applications

Product Name	V-30
Description	Aesthetically Refined, Shrouded Heat Sink, High-Powered LED Track Light with Integral Driver
Material	Die Cast Aluminium Alloy Body and Trim, Parabolic Anti-Glare Reflector, Aluminium Netted Heat Sink, Clear Tempered Glass Diffuser
Dimensions	Diameter: 90mm; Height: 134mm
LED Details	30W Sharp LED, 3000K or 4000K available, CRI: 90, Beam Angle: 24° or 60°, 3000lm
Driver	Integral Driver
IP Rating	IP20
IK Rating	IK03
Installation	Track Mounted

We reserve the right to make technical changes.

Should you have any enquiries, please consult an Actwell representative. Email: sales@actwelllighting.com.au
34 Mary Parade | Rydalmere NSW 2116 | Australia | T +61 2 9638 3333 | www.actwelllighting.com

TECHNICAL INFORMATION

Order Code:


AW4131TR-(Colour Finish)-(Temperature)-(Beam Angle)-(Dimming)

Example: AW4131TR-WH-3K-24°-ND



Options:

Colour Finish	Temperature	Beam Angle	Dimming
WH (White)	3K (3000K)	24°	ND (Non-Dim)
BK (Black)	4K (4000K)	60°	PH (Phase)
			11 (1-10V)
			DD (DALI)

Dimensions Line Diagram:



Photometrics:

	h(m)	D(m)	Em(lx)	Emax(lx)		h(m)	D(m)	Em(lx)	Emax(lx)
				24°					60°
	1	0.4	3400	13601		1	0.9	863	3452
	2	0.8	1190	3400		2	1.9	302	863
	3	1.1	680	1511		3	2.8	173	384
	4	1.5	468	850		4	3.8	119	216
	5	1.9	354	544		5	4.7	90	138

We reserve the right to make technical changes.

Should you have any enquiries, please consult an Actwell representative. Email: sales@actwelllighting.com.au

34 Mary Parade | Rydalmere NSW 2116 | Australia | T +61 2 9638 3333 | www.actwelllighting.com

TECHNICAL INFORMATION

Product Application Photo:

