

TECHNICAL INFORMATION

AW6218-3RD **Juno 25**



Recessed
Fixed

Application Descriptions:

- Recessed, Fixed
- Interior and Exterior Areas
- Undercover Awnings, Walkways, Corridors, Lobbies, Retail and Hospitality Commercial Offices, Educational and Medical Buildings, Aged Care Facility Applications

Product Name	JUNO 25
Description	Wide Beam Distribution, Low Profile, Frosted Lens, Fixed, Recessed LED Downlight
Material	Aluminium Trim and Body, Tempered Full Frosted Diffuser, Parabolic Reflector, Silicon Rubber Ring
Dimensions	Diameter: 195mm; Height: 65mm; Cut Out: 170mm
LED Details	25W Epistar COB, 3000K or 4000K available, CRI: 80, Beam Angle: 100°, 2300lm
Driver	500mA LED Driver
IP Rating	IP44
IK Rating	IK03
Installation	Recessed

We reserve the right to make technical changes.

Should you have any enquiries, please consult an Actwell representative. Email: sales@actwelllighting.com.au
34 Mary Parade | Rydalmere NSW 2116 | Australia | T +61 2 9638 3333 | www.actwelllighting.com

TECHNICAL INFORMATION

Order Code:

AW6218-3RD-(Colour Finish)-(Temperature)-(Beam Angle)-(Dimming)

Example: AW6218-3RD-WH-3K-100°-ND

Options:

Colour Finish	Temperature	Beam Angle	Dimming
WH (White)	3K (3000K)	100°	ND (Non-Dim)
	4K (4000K)		PH (Phase)
			11 (1-10V)
			DD (DALI)

Dimensions Line Diagram:

