

TECHNICAL INFORMATION

AW93RD Decatur 20



Recessed
Fixed

Application Descriptions:

- Recessed, Fixed
- Internal Areas, Low Glare Applications, General Ceiling Heights
- Retail, Shopping Malls, Hospitality, Hospitals, Aged Care, Schools, Theatres, and Commercial Office Applications

Product Name	DECATUR 20
Description	Dark Light Glare Control Reflector, Anti Glare Deep Baffle, Superior CRI, Fixed, Recessed LED Downlight
Material	Die Cast Aluminium Trim and Body, Cast Aluminium Heat Sink Rods for Maximal Heat Dissipation, Parabolic Reflector, Clear Glass Diffuser, Anodised Satin Matt Dark Light Reflector
Dimensions	Diameter: 150mm; Height: 166mm; Cut Out: 133mm
LED Details	20W Sharp Zenigata, 3000K or 4000K available, CRI: 91, Beam Angle: 36° or 60°, 1800lm
Driver	500mA LED Driver
IP Rating	IP20
IK Rating	IK03
Installation	Recessed

We reserve the right to make technical changes.

Should you have any enquiries, please consult an Actwell representative. Email: sales@actwelllighting.com.au
34 Mary Parade | Rydalmere NSW 2116 | Australia | T +61 2 9638 3333 | www.actwelllighting.com

TECHNICAL INFORMATION

Order Code:

AW93RD-(Colour Finish)-(Temperature)-(Beam Angle)-(Dimming)

Example: AW93RD-WH-3K-36°-ND



Options:

Colour Finish	Temperature	Beam Angle	Dimming
WH (White)	3K (3000K)	36°	ND (Non-Dim)
	4K (4000K)	60°	PH (Phase)
			11 (1-10v)
			DD (Dali)

Dimensions Line Diagram:



Photometrics:

	h(m)	D(m)	Em(lx)	Emax(lx)		h(m)	D(m)	Em(lx)	Emax(lx)
				36°					60°
	1	0.6	808	3232		1	0.9	550	2198
	2	1.2	283	808		2	1.8	193	550
	3	1.9	162	359		3	2.7	110	244
	4	2.5	111	202		4	3.6	75	137
	5	3.1	84	129		5	4.5	57	88

We reserve the right to make technical changes.

Should you have any enquiries, please consult an Actwell representative. Email: sales@actwelllighting.com.au

34 Mary Parade | Rydalmere NSW 2116 | Australia | T +61 2 9638 3333 | www.actwelllighting.com